

What is claimed is:

1. A method for conducting a plurality of assays for a plurality of different analytes in a carrier that may contain said different analytes, comprising:

providing a surface plasmon resonance active surface;

associating a plurality of different extended coupling matrices to said surface;

contacting said surface with said carrier, wherein the presence or absence of a specific analyte results in an increase, a decrease or no change in the indices of refraction of said extended coupling surfaces;

detecting said changes in said indices of refraction by measuring the SPR profile, wherein the SPR profile is distinguishable between said different extended coupling matrices.

2. The method of claim 1 wherein said active surface is a thin metal film.
3. The method of claim 2 wherein said thin metal film is selected from the group consisting of gold, copper, silver, aluminum.
4. The method of claim 1 wherein coupling matrices are covalently bound through sulfur bonds to alkyl chains of length from 2 to

20 carbons.

5. The method of claim 4 wherein coupling matrices comprise of atoms selected from the group consisting of gold, platinum, palladium, silver, aluminum, and copper.

5 6. The method of claim 1 wherein said carrier is air.

7. The method of claim 1 wherein said analytes are selected from the group consisting of chemical agent, biological agent and toxic industrial chemical.

8. An apparatus for sensing the amount, concentration or presence
10 of a substance through optically monitoring simultaneous increases in refractive index at positive layers, no change in refractive index at nonreactive layers, and decreases in refractive index at negative layers.

15

20

25